

Technical data sheet

WALLCOVERINGS ADHESIVE

extra strong



Power adhesive for all kind of wallpapers

Net quantity: 200g

Date: September 2022

Product description

Power adhesive for all kind of wallpapers. Non-woven wallpaper, embossed wallpaper, textile and glassfibre wall covering. Suitable for pasting machines.

Product properties

- Strong initial tack
- Does not stain
- High yield
- Very good open time, easy to correct
- Strong joint adhesion
- Ready for action within 15 minutes after dilution
- For pasting machines and application directly on the wall with roll or brush

Base	mixed technical powder adhesive
Appearance and color	white powder
Percentage of solid	100%
pH	7.6 - 7.7
Viscosity	14.000 - 15.000 cps
Custom code	39123920
Open time	30/40 minutes
Application temperature	+ 5°C to + 40°C
Seeting time	48 hours

Suitable for

- Woodchip wall coverings
- Non-woven wall coverings
- Vinyl and embossed wall coverings
- Fiberglass and contract wall coverings
- Foam backing wall coverings or non-woven fabric wallpapers

Storage

- The product is guaranteed for 60 months from the date of production
- Do not freeze
- Store in a dry place

Technical data sheet

WALLCOVERINGS ADHESIVE extra strong



Date: September 2022

Surface preparation

The surface must be of a single colour and uniformly light, dry, neutral, firm, clean, absorbent and even. Remove old wallpaper completely. For optimum wallpapering results, we recommend that you apply paint substrate Pro 150 before wallpapering.

Preparation and yield of adhesive

Dilute the product in clean water:

- approx. 4 liters for heavy wallcoverings with glass beads or granite = 20 m²
- approx. 4,5 - 5 liters for standard non-woven wallcoverings = 30 m²

1. Vigorously mix the water;
2. Dilute the contents of the bag in cold water, stirring continuously;
3. Wait 3 minutes;
4. Mix again;
5. The product is ready for use after 15 minutes.

Note: If the mixed paste drips viscously from the brush, it is ready for processing.



Application with roller

Apply the product directly on the wall with a suitable paste roller. Then proceed according to our wallpapering instructions, it's available online at <https://www.hohenberger-wallcoverings.com/media/48/81/e5/1648627387/Tapezieranleitung.pdf>

Excellent workability with pasting machines.

Cleaning

Clean possible spills with a damp sponge, dab carefully. The product does not stain

Contraindications

The product is not suitable for non-absorbent substrates, humid walls with mold or on surfaces not perfectly prepared. Spillage of the adhesive should be removed when the glue is still wet.

Final provisions

You will find high-quality wallpapering and painting accessories as well as the paint substrate Pro 150 in our online store at <https://www.hohenberger-wallcoverings.com/en/Shop/Accessories/>

 **Keep out of the reach of children and pets. Discharge the waste in special containers for building materials**

